

## TECHNICAL DATA SHEET

**PRODUCT** 24-7 RACE FUELS – OCTANE BOOSTER

### DESCRIPTION

Street Legal - Oxygenated Octane Booster Suited for 4/5/6/8 cylinder Normally Aspirated / Turbo Charged and Forced Induction motors. Product to be mixed as per ratio 1:4 / 1:5 to obtain desired octane fuel. Product contains corrosion inhibitor and valve seat recession additive

### PRODUCT RATIOS

**102RON:** [1:4] 5L TO 20L UNLEADED 95

**98RON:** [1:5] 5L TO 25L UNLEADED 95

Properties	Unit	Typical Results	Test Methods
Appearance	--	Clear Liquid	Visual
Colour	--	Light Blue	ASTM D1500
Specific Gravity @ 15°C	--	0.793	ASTM D1298
Total Purity by GLC	%	99.99	GLC In-House Method
Flash Point	°C	11-14	ASTM D93
Water Content	PPM	Nil	ASTM D6304
RON	--	104	ASTM 2699
MON	--	98	ASTM 2700
R+M/2	--	101	--

- All tests have been performed using the latest revision of the methods indicated unless specifically marked otherwise.
- This test report shall not be reproduced (except in full) without the written approval of the laboratory.
- This report is computer generated so signature and stamp not necessary.
- Air/Fuel Ratio, Turbo Pressure and Ignition Advance must be examined and re-tuned to reach optimum performance. Ignition and Injection mapping are strongly recommended. It is not recommended to mix our fuels with other additives or fuel blends / brands. To maintain the stated properties of the fuel, the fuel must be stored according to local legislation in a dark cool place. Containers / Drums must be sealed tightly.